



Model # 0199

TURBO-ADA™

ADA-Compliant High-Speed Automatic Hand Dryer



That's right. It's high speed and ADA compliant – without the need for an extra recess kit. At only 4" (102 mm) deep, this American Specialties, Inc. high-speed hand dryer complies with the very stringent 2010 ADA Accessibility Standards.

- Quick drying — less than 15 seconds
- Operates automatically using infrared sensor
- Auto-resetting thermostat
- Owner-adjustable air speed and air temperature
- On/off heating options
- Dryer automatically shuts off after time-out when user removes hands from sensor zone
- White cover is standard. Optional finishes include Bright or Satin Stainless Steel



SPECIFICATIONS

ADA Compliant Surface Mounted High-Speed Hand Dryer shall operate automatically from IR sensor activated by beam reflection from objects placed in sensing zone. Motor and heating element shall have internal resetting automatic thermal protection. Unit shall develop 60 CFM (102 m³/h) of heated air and shall provide drying time of less than 15 seconds. Cover shall be heavy-duty, one piece formed 18 gauge stainless steel bright or satin finished on all exposed surfaces (by option specified) or heavy-duty, one piece formed 18 gauge steel finished on all exposed surfaces with white porcelain enamel. Fixed directional air nozzle shall be heavy-duty, rust proof and highly tamper resistant. Air intake slots shall not allow access to internal parts. Circuitry shall have self-adjusting time-out and fail-safe off protection controlled by a microprocessor that shall detect and reject false signals and shall automatically self-calibrate to provide uniform sensitivity over its entire life span. Entire unit shall be internally electrically grounded. Dryer unit shall have C-UL-US® and CE approval and be listed under the re-examination services of Underwriters Laboratories, Inc. Unit shall be warranted against defects in materials or workmanship for five (5) years. Complete Owner's Manual (OM) and Installation Guide (IG) shall be provided with unit.

RATINGS								
MODEL	TYPE	AIR VELOCITY	TIMING SAFETY	SUPPLY		AMPS (MAX)	WATTS X1000	*COLOR
				AC VOLTS	HERTZ (HZ)			
0199-1	Hand	150 ~ 230ft/S 45.5~ 70 m/s	Automatic 60 second Shut-Off	115-120	50/60	10.4	0.84 – 1.0	Standard White Optional SS Bright SS Satin
0199-2				208-240	50/60	5.2	0.75 – 1.0	
0199-3				277	50/60	5.2	1.0	

MOTOR	H/P	RPM	FAN TYPE	HEATING ELEMENT	CFM m ³ /h	HEAT TEMP
Brush Type Dual Ball Bearings	0.67	16-29 (ADJ)	Multi-Inlet Centrifugal	325-450 Watt with auto reset circuit breaker Range Adjustable by Owner	42-60 (71-102)	131° F ± 5 @ 77° F (55° C ± 2.8 @ 25° C) Ambient room temperature

NET WT	SHIP WT	DRYING TIME	SENSING RANGE	SAFETY	WATER PROTECTION
8.4 lbs 3.8 kg	9.2 lbs 4.2 kg	Less than 15 seconds	Standard = 6" ± 25/32" (152 ± 20)	C-UL-US®, CE	Drip Proof IP23

SENSOR TYPE	DRYING PERSISTENCE	MOTOR THERMAL PROTECTION	HEATER THERMAL PROTECTION	SOUND PRESSURE
IR 780 nm Self-adjusting	Automatic 2 second Hold-On Shut-Off delay	120v Shut off @ > 275 °F {> 135 °C} 240v Shut off @ > 203 °F {< 95 °C}	Shut off @ > 185 °F {> 85 °C} Reset on @ < 167 °F {< 75 °C}	74.0 dB-A Maximum @ 2M



American Specialties, Inc.
441 Saw Mill River Rd, Yonkers, NY 10701
Tel: 914.476.9000 Fax: 914.476.0688
E-mail: info@americanspecialties.com Web: americanspecialties.com

